



## PRODUCT SPECIFICATION

### TFT MODULE

MODEL: LT-035320240-H01N      Rev A

---

| CUSTOMER APPROVAL |      |
|-------------------|------|
| SIGNATURE         | DATE |
|                   |      |

| PREPARED | CHECKED | APPROVED |
|----------|---------|----------|
|          |         |          |

**Revision History**

| Revision | Date       | Originator | Detail          | Remarks |
|----------|------------|------------|-----------------|---------|
| A        | 2019.05.31 |            | Initial Release |         |
|          |            |            |                 |         |
|          |            |            |                 |         |
|          |            |            |                 |         |
|          |            |            |                 |         |
|          |            |            |                 |         |
|          |            |            |                 |         |
|          |            |            |                 |         |
|          |            |            |                 |         |
|          |            |            |                 |         |

## Table of Contents

| No.   | Item                                                               | Page |
|-------|--------------------------------------------------------------------|------|
| 1.    | General Description.....                                           | 3    |
| 2.    | Module Parameter.....                                              | 3    |
| 3.    | Absolute Maximum Ratings.....                                      | 3    |
| 4.    | DC Characteristics.....                                            | 4    |
| 5.    | Backlight Characteristic.....                                      | 4    |
| 5.1.  | Backlight Characteristics.....                                     | 4    |
| 5.2.  | Backlighting circuit.....                                          | 4    |
| 6.    | Optical Characteristics.....                                       | 5    |
| 6.1.  | Optical Characteristics.....                                       | 5    |
| 6.2.  | Definition of Response Time.....                                   | 5    |
| 6.3.  | Definition of Contrast Ratio.....                                  | 6    |
| 6.4.  | Definition of Viewing Angles.....                                  | 6    |
| 6.5.  | Definition of Color Appearance.....                                | 7    |
| 6.6.  | Definition of Surface Luminance, Uniformity and Transmittance..... | 7    |
| 7.    | Block Diagram and Power Supply.....                                | 8    |
| 8.    | Interface Pins Definition.....                                     | 9    |
| 9.    | AC Characteristics.....                                            | 11   |
| 10.   | Quality Assurance.....                                             | 17   |
| 10.1. | Purpose.....                                                       | 17   |
| 10.2. | Standard for Quality Test.....                                     | 17   |
| 10.3. | Nonconforming Analysis & Disposition.....                          | 17   |
| 10.4. | Agreement Items.....                                               | 17   |
| 10.5. | Standard of the Product Visual Inspection.....                     | 17   |
| 10.6. | Inspection Specification.....                                      | 18   |
| 10.7. | Classification of Defects.....                                     | 22   |
| 10.8. | Identification/marketing criteria.....                             | 22   |
| 10.9. | Packing.....                                                       | 22   |
| 11.   | Reliability Specification.....                                     | 23   |
| 12.   | Precautions and Warranty.....                                      | 24   |
| 12.1. | Safety.....                                                        | 24   |
| 12.2. | Handling.....                                                      | 24   |
| 12.3. | Storage.....                                                       | 24   |
| 12.4. | Metal Pin (Apply to Products with Metal Pins).....                 | 24   |
| 12.5. | Operation.....                                                     | 25   |
| 12.6. | Static Electricity.....                                            | 25   |
| 12.7. | Limited Warranty.....                                              | 25   |
| 13.   | Packaging.....                                                     | 26   |
| 14.   | Outline Drawing.....                                               | 27   |

## 1. General Description

The specification is a transmissive type color active matrix liquid crystal display (LCD) which uses amorphous thin film transistor (TFT) as switching devices. This product is composed of a TFT-LCD panel, driver ICs and a backlight unit.

## 2. Module Parameter

| Features                       | Details                             | Unit       |
|--------------------------------|-------------------------------------|------------|
| Display Size(Diagonal)         | 3.5"                                |            |
| LCD type                       | TN TFT                              |            |
| Display Mode                   | Transmissive /Normally white        |            |
| Resolution                     | 320 RGB x 240                       | Pixels     |
| View Direction                 | 12 O'clock                          | Best Image |
| Gray Scale Inversion Direction | 6 O'clock                           |            |
| Module Outline                 | 76.9(H) x 63.9(V) x 3.3(T) (Note1 ) | mm         |
| Active Area                    | 70.08(H) x 52.56(V)                 | mm         |
| Pixel Size                     | 219(H) x219(V)                      | um         |
| Pixel Arrangement              | RGB stripe                          |            |
| Polarizer Surface Treatment    | Anti-glare                          |            |
| Display Colors                 | 16.7M                               |            |
| Interface                      | 24-bit RGB Interface+3 wire SPI     |            |
| Driver IC                      | HX8238D                             | -          |
| With or Without Touch Panel    | Without                             |            |
| Operating Temperature          | <b>-20~70</b>                       | °C         |
| Storage Temperature            | <b>-30~80</b>                       | °C         |
| Weight                         | 32                                  | g          |

Note 1: Exclusive hooks, posts, FFC/FPC tail etc.

## 3. Absolute Maximum Ratings

V<sub>SS</sub>=0V, Ta=25°C

| Item                  | Symbol           | Min.       | Max.       | Unit |
|-----------------------|------------------|------------|------------|------|
| Supply Voltage        | VDD              | -0.3       | 5.0        | V    |
| Storage temperature   | T <sub>stg</sub> | <b>-30</b> | <b>+80</b> | °C   |
| Operating temperature | T <sub>op</sub>  | <b>-20</b> | <b>+70</b> | °C   |

Note 1: If Ta below 50°C, the maximal humidity is 90%RH, if Ta over 50°C, absolute humidity should be less than 60%RH.

Note 2: The response time will be extremely slow when the operating temperature is around -10°C, and the back ground will become darker at high temperature operating.

#### 4. DC Characteristics

| Item                             | Symbol          | Min.    | Typ. | Max.    | Unit |
|----------------------------------|-----------------|---------|------|---------|------|
| Supply Voltage                   | VDD             | 3.0     | 3.3  | 3.6     | V    |
| Logic Low input voltage          | V <sub>IL</sub> | GND     | -    | 0.2*VDD | V    |
| Logic High input voltage         | V <sub>IH</sub> | 0.8*VDD | -    | VDD     | V    |
| Logic Low output voltage         | V <sub>OL</sub> | GND     | -    | 0.1*VDD | V    |
| Logic High output voltage        | V <sub>OH</sub> | 0.9*VDD | -    | VDD     | V    |
| Current Consumption<br>All Black | Logic           | -       | 18   | 30      | mA   |
|                                  | Analog          |         |      |         |      |

#### 5. Backlight Characteristic


##### 5.1. Backlight Characteristics

| Item                   | Symbol                 | Condition                          | Min. | Typ.        | Max. | Unit |
|------------------------|------------------------|------------------------------------|------|-------------|------|------|
| Forward Voltage        | V <sub>F</sub>         | Ta=25 °C, I <sub>F</sub> =20mA/LED | 17.4 | <b>19.2</b> | 19.8 | V    |
| Forward Current        | I <sub>F</sub>         | Ta=25 °C, V <sub>F</sub> =3.2V/LED | -    | <b>20</b>   | -    | mA   |
| Power dissipation      | P <sub>d</sub>         |                                    | -    | 384         | -    | mW   |
| Uniformity             | Avg                    |                                    | 80   | -           | -    | %    |
| LED working life(25°C) | -                      |                                    | -    | 20000       | -    | Hrs  |
| Drive method           | Constant current       |                                    |      |             |      |      |
| LED Configuration      | 6 White LEDs in series |                                    |      |             |      |      |

Note1: LED life time defined as follows: The final brightness is at 50% of original brightness.

The environmental conducted under ambient air flow, at Ta=25±2 °C, 60%RH±5%, I<sub>F</sub>=20mA/LED.

##### 5.2. Backlighting circuit



## 6. Optical Characteristics


### 6.1. Optical Characteristics

$T_a=25^{\circ}\text{C}$ ,  $V_{DD}=3.3\text{V}$

| Backlight On (Transmissive Mode) | Item                                |            | Symbol         | Condition                                                  | Specification |       |       | Unit              |
|----------------------------------|-------------------------------------|------------|----------------|------------------------------------------------------------|---------------|-------|-------|-------------------|
|                                  |                                     |            |                |                                                            | Min.          | Typ.  | Max.  |                   |
|                                  | Luminance on TFT( $I_f$ =20mA/LED)  |            | Lv             | Normally viewing angle<br>$\theta_X = \varphi_Y = 0^\circ$ | 320           | 400   | -     | cd/m <sup>2</sup> |
|                                  | Contrast ratio(See 6.3)             |            | CR             |                                                            | 300           | 350   | -     |                   |
|                                  | Response time (See 6.2)             |            | Tr+Tf          |                                                            | -             | 25    | -     | ms                |
|                                  | Chromaticity Transmissive (See 6.5) | Red        | Xr             |                                                            | 0.558         | 0.608 | 0.658 |                   |
|                                  |                                     |            | Yr             |                                                            | 0.314         | 0.364 | 0.414 |                   |
|                                  |                                     | Green      | Xg             |                                                            | 0.266         | 0.316 | 0.366 |                   |
|                                  |                                     |            | Yg             |                                                            | 0.574         | 0.624 | 0.674 |                   |
|                                  |                                     | Blue       | Xb             |                                                            | 0.092         | 0.142 | 0.192 |                   |
|                                  |                                     |            | Yb             |                                                            | 0.032         | 0.082 | 0.132 |                   |
|                                  |                                     | White      | Xw             |                                                            | 0.233         | 0.283 | 0.333 |                   |
|                                  |                                     |            | Yw             |                                                            | 0.271         | 0.321 | 0.371 |                   |
|                                  | Viewing Angle (See 6.4)             | Horizontal | $\theta_{X+}$  | Center CR≥10                                               | -             | (55)  | -     | Deg.              |
|                                  |                                     |            | $\theta_{X-}$  |                                                            | -             | (55)  | -     |                   |
|                                  |                                     | Vertical   | $\varphi_{Y+}$ |                                                            | -             | (45)  | -     |                   |
| $\varphi_{Y-}$                   |                                     |            | -              |                                                            | (50)          | -     |       |                   |
| NTSC Ratio(Gamut)                |                                     |            |                | -                                                          | 60            | -     | %     |                   |

### 6.2. Definition of Response Time

#### 6.2.1. Normally Black Type (Negative)




$T_r$  is the time it takes to change from non-selected stage with relative luminance 10% to selected state with relative luminance 90%;

Tf is the time it takes to change from selected state with relative luminance 90% to non-selected state with relative luminance 10%.

Note: Measuring machine: LCD-5100

#### 6.2.2. Normally White Type (Positive)



Tr is the time it takes to change from non-selected stage with relative luminance 90% to selected state with relative luminance 10%;

Tf is the time it takes to change from selected state with relative luminance 10% to non-selected state with relative luminance 90%;

Note: Measuring machine: LCD-5100 or EQUI

#### 6.3. Definition of Contrast Ratio


Contrast is measured perpendicular to display surface in reflective and transmissive mode.

The measurement condition is:

|                          |                          |
|--------------------------|--------------------------|
| Measuring Equipment      | Eldim or Equivalent      |
| Measuring Point Diameter | 3mm//1mm                 |
| Measuring Point Location | Active Area centre point |
| Test pattern             | A: All Pixels white      |
|                          | B: All Pixel black       |
| Contrast setting         | Maximum                  |

Definitions: CR (Contrast) = Luminance of White Pixel / Luminance of Black Pixel

#### 6.4. Definition of Viewing Angles




Measuring machine: LCD-5100 or EQUI

### 6.5. Definition of Color Appearance

R,G,B and W are defined by (x, y) on the IE chromaticity diagram

NTSC=area of RGB triangle/area of NTSC triangleX100%

Measuring picture: Red, Green, Blue and White (Measuring machine: BM-7)



### 6.6. Definition of Surface Luminance, Uniformity and Transmittance


Using the transmissive mode measurement approach, measure the white screen luminance of the display panel and backlight.

6.6.1. Surface Luminance:  $L_V = \text{average } (L_{P1}:L_{P9})$

6.6.2. Uniformity = Minimal ( $L_{P1}:L_{P9}$ ) / Maximal ( $L_{P1}:L_{P9}$ ) \* 100%


6.6.3. Transmittance =  $L_V$  on LCD /  $L_V$  on Backlight \* 100%

Note: Measuring machine: BM-7





## 7. Block Diagram and Power Supply



## 8. Interface Pins Definition

| No.   | Symbol | Function                      |
|-------|--------|-------------------------------|
| 1-2   | LED_K  | LED cathode                   |
| 3-4   | LED_A  | LED anode                     |
| 5     | NC(YU) | No connect                    |
| 6     | NC(XR) | No connect                    |
| 7     | NC     | No connect                    |
| 8     | RESET  | Reset signal, Low active      |
| 9     | /CS    | Chip select                   |
| 10    | SCK    | SPI Serial Clock              |
| 11    | SDI    | SPI Serial Data Input/output  |
| 12    | B0     | Data bus                      |
| 13    | B1     | Data bus                      |
| 14    | B2     | Data bus                      |
| 15    | B3     | Data bus                      |
| 16    | B4     | Data bus                      |
| 17    | B5     | Data bus                      |
| 18    | B6     | Data bus                      |
| 19    | B7     | Data bus                      |
| 20    | G0     | Data bus                      |
| 21    | G1     | Data bus                      |
| 22    | G2     | Data bus                      |
| 23    | G3     | Data bus                      |
| 24    | G4     | Data bus                      |
| 25    | G5     | Data bus                      |
| 26    | G6     | Data bus                      |
| 27    | G7     | Data bus                      |
| 28    | R0     | Data bus                      |
| 29    | R1     | Data bus                      |
| 30    | R2     | Data bus                      |
| 31    | R3     | Data bus                      |
| 32    | R4     | Data bus                      |
| 33    | R5     | Data bus                      |
| 34    | R6     | Data bus                      |
| 35    | R7     | Data bus                      |
| 36    | HSYNC  | Horizontal Synchronous Signal |
| 37    | VSYNC  | Vertical Synchronous Signal   |
| 38    | DOTCLK | Data Clock                    |
| 39-40 | NC     | No connect                    |
| 41-42 | VDD    | Power Supply                  |
| 43    | NC(YD) | No connect                    |
| 44    | NC(XL) | No connect                    |

|       |          |                               |
|-------|----------|-------------------------------|
| 45-47 | NC       | No connect                    |
| 48    | NC(SEL2) | No connect                    |
| 49    | NC(SEL1) | No connect                    |
| 50    | NC(SEL0) | No connect                    |
| 51    | NC       | No connect                    |
| 52    | DEN      | Data enabling signal          |
| 53    | GND      | Ground                        |
| 54    | AVSS     | Grounding for analog circuit. |

## 9. AC Characteristics





Figure 1: Pixel Timing

| Characteristics                              | Symbol  | Min.   |       | Typ.   |       | Max.   |       | Unit    |
|----------------------------------------------|---------|--------|-------|--------|-------|--------|-------|---------|
|                                              |         | 24 bit | 8 bit | 24 bit | 8 bit | 24 bit | 8 bit |         |
| DOTCLK Frequency                             | fDOTCLK | -      | -     | 6.5    | 19.5  | 10     | 30    | MHz     |
| DOTCLK Period                                | tDOTCLK | 100    | 33.3  | 154    | 51.3  | -      | -     | ns      |
| Vertical Sync Setup Time                     | tvsys   | 20     | 10    | -      | -     | -      | -     | ns      |
| Vertical Sync Hold Time                      | tvsyh   | 20     | 10    | -      | -     | -      | -     | ns      |
| Horizontal Sync Setup Time                   | thsys   | 20     | 10    | -      | -     | -      | -     | ns      |
| Horizontal Sync Hold Time                    | thsyh   | 20     | 10    | -      | -     | -      | -     | ns      |
| Phase difference of Sync Signal Falling Edge | thv     | 1      |       | -      |       | 240    |       | tDOTCLK |
| DOTCLK Low Period                            | tCKL    | 50     | 15    | -      | -     | -      | -     | ns      |
| DOTCLK High Period                           | tCKH    | 50     | 15    | -      | -     | -      | -     | ns      |
| Data Setup Time                              | tds     | 12     | 10    | -      | -     | -      | -     | ns      |
| Data hold Time                               | tdh     | 12     | 10    | -      | -     | -      | -     | ns      |
| Reset pulse width                            | tRES    | 10     |       | -      |       | -      |       | $\mu s$ |

**Note:** External clock source must be provided to DOTCLK pin of HX8238-D. The driver will not operate if absent of the clocking signal.

Table 1: Pixel Timing



### Vertical input Format




Figure 2: Data Transaction Timing in Parallel RGB(24 bit) Interface(DE Mode)

### Timing Characteristics

#### Horizontal input timing

| Parameter                |      | Symbol | Value |      |      | Unit |
|--------------------------|------|--------|-------|------|------|------|
|                          |      |        | Min.  | Typ. | Max. |      |
| Horizontal display area  |      | thd    | 320   |      |      | DCLK |
| DCLK frequency           |      | fclk   | -     | 7    | -    | MHZ  |
| 1 Horizontal Line        |      | th     | 409   |      |      | DCLK |
| HSD pulse width          | Typ. | 1      |       |      |      |      |
| HSD Back Porch(Blanking) |      | thb    | -     | 70   | -    |      |
| HSD Front Porch          |      | thfp   | -     | 18   | -    |      |

## Vertical input timing

| Parameter                | Symbol          | Value |      |      | Unit |
|--------------------------|-----------------|-------|------|------|------|
|                          |                 | Min.  | Typ. | Max. |      |
| Vertical display area    | tv <sub>d</sub> | 240   |      |      | H    |
| VSD period time          | tv              | -     | 263  | -    | H    |
| VSD pulse width          | tpw             | -     | 1    | -    | H    |
| VSD Back Porch(Blanking) | tvb             | -     | 13   | -    | H    |
| VSD Front Porch          | tvfp            | -     | 10   | -    | H    |

Table 2: Data Transaction Timing in DE Mode




Figure 4: Power Up Sequence

| Characteristics                                                                                        | Symbol     | Spec. |      |       | Unit    |
|--------------------------------------------------------------------------------------------------------|------------|-------|------|-------|---------|
|                                                                                                        |            | Min.  | Typ. | Max.  |         |
| VDDD / VDDIO on to falling edge of SHUT                                                                | tp-shut    | 1     | -    | -     | $\mu$ s |
| DOTCLK                                                                                                 | tcclk-shut | 1     | -    | -     | clk     |
| Falling edge of SHUT to display start<br>- 1 line: 408 clk<br>- 1 frame: 262 line<br>- DOTCLK = 6.5MHz | tshut-on   | -     | -    | 14    | frame   |
|                                                                                                        |            | -     | 166  | 232.4 | ms      |

**Note:** It is necessary to input DOTCLK before the falling edge of SHUT.  
Display starts at 10th falling edge of VSTNC after the falling edge of SHUT.

Table 3: Power Up Sequence




Figure 5: Power Down Sequence



| Characteristics                                               | Symbol    | Spec. |      |      | Unit  |
|---------------------------------------------------------------|-----------|-------|------|------|-------|
|                                                               |           | Min.  | Typ. | Max. |       |
| Rising edge of SHUT to display off                            | tshut-off | 2     | -    | -    | frame |
| - 1 line: 408 clk<br>- 1 frame: 262 line<br>- DOTCLK = 6.5MHz |           | 33.4  | -    | -    | ms    |


**Note:** DOTCLK must be maintained at least 2 frames after the rising edge of SHUT.

Display become off at the 2nd falling edge of VSTNC after the falling edge of SHUT.

If RESET signal is necessary for power down, provide it after the 2-frames-cycle of the SHUT period.

Table 4: Power Down Sequence

### • Write SPI



**Note:** The example writes "0x1264h" to register R28h.  
SPID connected to VSS.

Figure 6: (a) SPI interface Timing Diagram & Write SPI Example



- Read SPI




Figure 7:(b) SPI interface Timing Diagram &amp; Read SPI Example




Figure 8: Rising/Falling Time

| Characteristics             | Symbol | Spec. |      |      | Unit |
|-----------------------------|--------|-------|------|------|------|
|                             |        | Min.  | Typ. | Max. |      |
| Serial Clock Frequency      | fclk   | -     | -    | 20   | MHz  |
| Serial Clock Cycle Time     | tclk   | 50    | -    | -    | ns   |
| Clock Low Width             | tsl    | 25    | -    | -    | ns   |
| Clock High Width            | tsh    | 25    | -    | -    | ns   |
| Clock Rising Time           | trs    | -     | -    | 30   | ns   |
| Clock Falling Time          | tfl    | -     | -    | 30   | ns   |
| Chip Select Hold Time       | tcsh   | 10    | -    | -    | ns   |
| Chip Select High Delay Time | tcsd   | 20    | -    | -    | ns   |
| Data Setup Time             | tds    | 5     | -    | -    | ns   |
| Data Hold Time              | tdh    | 10    | -    | -    | ns   |

Table 5: SPI Timing

## **10. Quality Assurance**

### **10.1.Purpose**

This standard for Quality Assurance assures the quality of LCD module products supplied to customer.

### **10.2.Standard for Quality Test**

#### 10.2.1. Sampling Plan:

GB2828.1-2012

Single sampling, general inspection level II

#### 10.2.2. Sampling Criteria:

Visual inspection: AQL 1.5%

Electrical functional: AQL 0.65%.

#### 10.2.3. Reliability Test:

Detailed requirement refer to Reliability Test Specification.

### **10.3.Nonconforming Analysis & Disposition**

#### 10.3.1. Nonconforming analysis:

10.3.1.1. Customer should provide overall information of non-conforming sample for their complaints.

10.3.1.2. After receipt of detailed information from customer, the analysis of nonconforming parts usually should be finished in one week.

10.3.1.3. If cannot finish the analysis on time, customer will be notified with the progress status.

#### 10.3.2. Disposition of nonconforming:

10.3.2.1. Non-conforming product over PPM level will be replaced.

10.3.2.2. The cause of non-conformance will be analyzed. Corrective action will be discussed and implemented.

### **10.4.Agreement Items**

Shall negotiate with customer if the following situation occurs:

10.4.1. There is any discrepancy in standard of quality assurance.

10.4.2. Additional requirement to be added in product specification.

10.4.3. Any other special problem.


### **10.5.Standard of the Product Visual Inspection**

#### 10.5.1. Appearance inspection:

10.5.1.1. The inspection must be under illumination about 1000 – 1500 lx, and the distance of view must be at 30cm ± 2cm.

10.5.1.2. The viewing angle should be 45° from the vertical line without reflection light or follows customer's viewing angle specifications.

## 10.5.1.3. Definition of area: A Zone: Active Area, B Zone: Viewing Area,






## 10.5.2. Basic principle:

10.5.2.1. A set of sample to indicate the limit of acceptable quality level must be discussed by both us and customer when there is any dispute happened.





10.5.2.2. New item must be added on time when it is necessary.


## 10.6. Inspection Specification

| No.                                                                   | Item                                                                                                              | Criteria (Unit: mm)                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                            |              |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
|-----------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------------|----------|------------------|--------|-------------------------|----------|-------------------------|------------|---------------|------------|------------|-------------------------------|------------------------------------|--|-------|
| 01                                                                    | Black / White spot<br>Foreign material (Round type)<br>Pinholes<br>Stain<br>Particles inside cell. (Minor defect) | <br>$\phi = (a + b) / 2$                                                                                                                                                                                                                                                                                                            | <table><tr><th>Size \ Area</th><th>Acc. Qty</th></tr><tr><td><math>\phi \leq 0.10</math></td><td>Ignore</td></tr><tr><td><math>0.10 &lt; \phi \leq 0.15</math></td><td>2</td></tr><tr><td><math>0.15 &lt; \phi \leq 0.25</math></td><td>1</td></tr><tr><td><math>0.25 &lt; \phi</math></td><td>0</td></tr><tr><td>Total</td><td>2 no include <math>\phi \geq 0.10</math></td></tr></table> |              | Size \ Area | Acc. Qty | $\phi \leq 0.10$ | Ignore | $0.10 < \phi \leq 0.15$ | 2        | $0.15 < \phi \leq 0.25$ | 1          | $0.25 < \phi$ | 0          | Total      | 2 no include $\phi \geq 0.10$ |                                    |  |       |
|                                                                       |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        | Size \ Area                                                                                                                                                                                                                                                                                                                                                                                | Acc. Qty     |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
|                                                                       |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        | $\phi \leq 0.10$                                                                                                                                                                                                                                                                                                                                                                           | Ignore       |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
|                                                                       |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        | $0.10 < \phi \leq 0.15$                                                                                                                                                                                                                                                                                                                                                                    | 2            |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
|                                                                       |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        | $0.15 < \phi \leq 0.25$                                                                                                                                                                                                                                                                                                                                                                    | 1            |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
| $0.25 < \phi$                                                         | 0                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                            |              |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
| Total                                                                 | 2 no include $\phi \geq 0.10$                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                            |              |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
| Distance between 2 defects should more than 3mm apart.                |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                            |              |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
| 02                                                                    | Electrical Defect (Minor defect)                                                                                  | <table><tr><td></td><td>Display Area</td><td>Total</td><td rowspan="4">Note1</td></tr><tr><td>Bright dot</td><td>0</td><td>0</td></tr><tr><td>Dark dot</td><td><math>N \leq 2</math></td><td><math>N \leq 2</math></td></tr><tr><td>Total dot</td><td><math>N \leq 2</math></td><td><math>N \leq 2</math></td></tr><tr><td>Mura</td><td colspan="2">Not visible through 5% ND filters.</td><td>Note2</td></tr></table> |                                                                                                                                                                                                                                                                                                                                                                                            | Display Area | Total       | Note1    | Bright dot       | 0      | 0                       | Dark dot | $N \leq 2$              | $N \leq 2$ | Total dot     | $N \leq 2$ | $N \leq 2$ | Mura                          | Not visible through 5% ND filters. |  | Note2 |
|                                                                       |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                            | Display Area | Total       |          | Note1            |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
|                                                                       |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        | Bright dot                                                                                                                                                                                                                                                                                                                                                                                 | 0            | 0           |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
|                                                                       |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        | Dark dot                                                                                                                                                                                                                                                                                                                                                                                   | $N \leq 2$   | $N \leq 2$  |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
|                                                                       |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        | Total dot                                                                                                                                                                                                                                                                                                                                                                                  | $N \leq 2$   | $N \leq 2$  |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
| Mura                                                                  | Not visible through 5% ND filters.                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                        | Note2                                                                                                                                                                                                                                                                                                                                                                                      |              |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
| Remark:                                                               |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                            |              |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
| 1. Bright dot caused by scratch and foreign object accords to item 1. |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                            |              |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |
|                                                                       |                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                            |              |             |          |                  |        |                         |          |                         |            |               |            |            |                               |                                    |  |       |

| 03           | Black and White line<br>Scratch<br>Foreign material<br>(Line type)<br>(Minor defect) |  <table border="1" data-bbox="592 750 1219 1059"> <thead> <tr> <th>Length</th><th>Width</th><th>Acc. Qty</th></tr> </thead> <tbody> <tr> <td>/</td><td><math>W \leq 0.03</math></td><td>Ignore</td></tr> <tr> <td><math>L \leq 2.5</math></td><td><math>0.03 &lt; W \leq 0.05</math></td><td>3</td></tr> <tr> <td><math>L \leq 2.5</math></td><td><math>0.05 &lt; W \leq 0.10</math></td><td>2</td></tr> <tr> <td>/</td><td><math>0.1 &lt; W</math></td><td>0</td></tr> <tr> <td colspan="2">Total</td><td>3</td></tr> </tbody> </table> <p>Distance between 2 defects should more than 3mm apart. Scratches not viewable through the back of the display are acceptable.</p> | Length | Width | Acc. Qty | / | $W \leq 0.03$ | Ignore | $L \leq 2.5$ | $0.03 < W \leq 0.05$ | 3 | $L \leq 2.5$ | $0.05 < W \leq 0.10$ | 2 | / | $0.1 < W$ | 0 | Total |  | 3 |
|--------------|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-------|----------|---|---------------|--------|--------------|----------------------|---|--------------|----------------------|---|---|-----------|---|-------|--|---|
| Length       | Width                                                                                | Acc. Qty                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |        |       |          |   |               |        |              |                      |   |              |                      |   |   |           |   |       |  |   |
| /            | $W \leq 0.03$                                                                        | Ignore                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |        |       |          |   |               |        |              |                      |   |              |                      |   |   |           |   |       |  |   |
| $L \leq 2.5$ | $0.03 < W \leq 0.05$                                                                 | 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |        |       |          |   |               |        |              |                      |   |              |                      |   |   |           |   |       |  |   |
| $L \leq 2.5$ | $0.05 < W \leq 0.10$                                                                 | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |        |       |          |   |               |        |              |                      |   |              |                      |   |   |           |   |       |  |   |
| /            | $0.1 < W$                                                                            | 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |        |       |          |   |               |        |              |                      |   |              |                      |   |   |           |   |       |  |   |
| Total        |                                                                                      | 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |        |       |          |   |               |        |              |                      |   |              |                      |   |   |           |   |       |  |   |
| 04           | Glass Crack<br>(Minor defect)                                                        |  <p>Crack is potential to enlarge, any type is not allowed.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |        |       |          |   |               |        |              |                      |   |              |                      |   |   |           |   |       |  |   |

| 05                           | Glass Chipping Pad Area:<br>(Minor defect) |                                                                                                                                                                                                                                                                          |                  |          |                    |   |                    |   |                              |
|------------------------------|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|----------|--------------------|---|--------------------|---|------------------------------|
|                              |                                            | <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td><math>c &gt; 3.0, b &lt; 1.0</math></td><td>1</td></tr><tr><td><math>c &lt; 3.0, b &lt; 1.0</math></td><td>3</td></tr><tr><td colspan="2"><math>a &lt; \text{Glass Thickness}</math></td></tr></table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1 | $c < 3.0, b < 1.0$ | 3 | $a < \text{Glass Thickness}$ |
| Length and Width             | Acc. Qty                                   |                                                                                                                                                                                                                                                                          |                  |          |                    |   |                    |   |                              |
| $c > 3.0, b < 1.0$           | 1                                          |                                                                                                                                                                                                                                                                          |                  |          |                    |   |                    |   |                              |
| $c < 3.0, b < 1.0$           | 3                                          |                                                                                                                                                                                                                                                                          |                  |          |                    |   |                    |   |                              |
| $a < \text{Glass Thickness}$ |                                            |                                                                                                                                                                                                                                                                          |                  |          |                    |   |                    |   |                              |

| 06                           | <p>Glass Chipping Rear of Pad Area:<br/>(Minor defect)</p>  | <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td><math>c &gt; 3.0, b &lt; 1.0</math></td><td>1</td></tr><tr><td><math>c &lt; 3.0, b &lt; 1.0</math></td><td>2</td></tr><tr><td><math>c &lt; 3.0, b &lt; 0.5</math></td><td>4</td></tr><tr><td colspan="2"><math>a &lt; \text{Glass Thickness}</math></td></tr></table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1      | $c < 3.0, b < 1.0$           | 2 | $c < 3.0, b < 0.5$ | 4 | $a < \text{Glass Thickness}$ |  |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|----------|--------------------|--------|------------------------------|---|--------------------|---|------------------------------|--|
| Length and Width             | Acc. Qty                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| $c > 3.0, b < 1.0$           | 1                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| $c < 3.0, b < 1.0$           | 2                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| $c < 3.0, b < 0.5$           | 4                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| $a < \text{Glass Thickness}$ |                                                                                                                                              |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| 07                           | <p>Glass Chipping Except Pad Area:<br/>(Minor defect)</p>   | <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td><math>c &gt; 3.0, b &lt; 1.0</math></td><td>1</td></tr><tr><td><math>c &lt; 3.0, b &lt; 1.0</math></td><td>2</td></tr><tr><td><math>c &lt; 3.0, b &lt; 0.5</math></td><td>4</td></tr><tr><td colspan="2"><math>a &lt; \text{Glass Thickness}</math></td></tr></table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1      | $c < 3.0, b < 1.0$           | 2 | $c < 3.0, b < 0.5$ | 4 | $a < \text{Glass Thickness}$ |  |
| Length and Width             | Acc. Qty                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| $c > 3.0, b < 1.0$           | 1                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| $c < 3.0, b < 1.0$           | 2                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| $c < 3.0, b < 0.5$           | 4                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| $a < \text{Glass Thickness}$ |                                                                                                                                              |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| 08                           | <p>Glass Corner Chipping:<br/>(Minor defect)</p>          | <table><tr><th>Length and Width</th><th>Acc. Qty</th></tr><tr><td><math>c &lt; 3.0, b &lt; 3.0</math></td><td>Ignore</td></tr><tr><td colspan="2"><math>a &lt; \text{Glass Thickness}</math></td></tr></table>                                                                                                                          | Length and Width | Acc. Qty | $c < 3.0, b < 3.0$ | Ignore | $a < \text{Glass Thickness}$ |   |                    |   |                              |  |
| Length and Width             | Acc. Qty                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| $c < 3.0, b < 3.0$           | Ignore                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| $a < \text{Glass Thickness}$ |                                                                                                                                              |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| 09                           | <p>Glass Burr:<br/>(Minor defect)</p>                     | <table><tr><th>Length</th><th>Acc. Qty</th></tr><tr><td><math>F &lt; 1.0</math></td><td>Ignore</td></tr></table> <p>Glass burr don't affect assemble and module dimension.</p>                                                                                                                                                          | Length           | Acc. Qty | $F < 1.0$          | Ignore |                              |   |                    |   |                              |  |
| Length                       | Acc. Qty                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |
| $F < 1.0$                    | Ignore                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                         |                  |          |                    |        |                              |   |                    |   |                              |  |

| 10                         | FPC Defect:<br>(Minor defect)<br> | 10.1 Dent, pinhole width $a < w/3$ .<br>(w: circuitry width.)<br>10.2 Open circuit is unacceptable.<br>10.3 No oxidation, contamination and distortion.                                                                                                                                                                                                                                                                                                     |          |          |                     |        |                            |   |                            |   |                  |      |
|----------------------------|--------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|----------|---------------------|--------|----------------------------|---|----------------------------|---|------------------|------|
| 11                         | Bubble on Polarizer<br>(Minor defect)                                                                              | <table><tr><th>Diameter</th><th>Acc. Qty</th></tr><tr><td><math>\varphi \leq 0.20</math></td><td>Ignore</td></tr><tr><td><math>0.20 &lt; \varphi \leq 0.30</math></td><td>4</td></tr><tr><td><math>0.30 &lt; \varphi \leq 0.50</math></td><td>1</td></tr><tr><td><math>0.50 &lt; \varphi</math></td><td>None</td></tr></table>                                                                                                                              | Diameter | Acc. Qty | $\varphi \leq 0.20$ | Ignore | $0.20 < \varphi \leq 0.30$ | 4 | $0.30 < \varphi \leq 0.50$ | 1 | $0.50 < \varphi$ | None |
| Diameter                   | Acc. Qty                                                                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |          |                     |        |                            |   |                            |   |                  |      |
| $\varphi \leq 0.20$        | Ignore                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |          |                     |        |                            |   |                            |   |                  |      |
| $0.20 < \varphi \leq 0.30$ | 4                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |          |                     |        |                            |   |                            |   |                  |      |
| $0.30 < \varphi \leq 0.50$ | 1                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |          |                     |        |                            |   |                            |   |                  |      |
| $0.50 < \varphi$           | None                                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |          |                     |        |                            |   |                            |   |                  |      |
| 12                         | Dent on Polarizer<br>(Minor defect)                                                                                | <table><tr><th>Diameter</th><th>Acc. Qty</th></tr><tr><td><math>\varphi \leq 0.20</math></td><td>Ignore</td></tr><tr><td><math>0.20 &lt; \varphi \leq 0.30</math></td><td>4</td></tr><tr><td><math>0.30 &lt; \varphi \leq 0.50</math></td><td>1</td></tr><tr><td><math>0.50 &lt; \varphi</math></td><td>None</td></tr></table>                                                                                                                              | Diameter | Acc. Qty | $\varphi \leq 0.20$ | Ignore | $0.20 < \varphi \leq 0.30$ | 4 | $0.30 < \varphi \leq 0.50$ | 1 | $0.50 < \varphi$ | None |
| Diameter                   | Acc. Qty                                                                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |          |                     |        |                            |   |                            |   |                  |      |
| $\varphi \leq 0.20$        | Ignore                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |          |                     |        |                            |   |                            |   |                  |      |
| $0.20 < \varphi \leq 0.30$ | 4                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |          |                     |        |                            |   |                            |   |                  |      |
| $0.30 < \varphi \leq 0.50$ | 1                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |          |                     |        |                            |   |                            |   |                  |      |
| $0.50 < \varphi$           | None                                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |          |                     |        |                            |   |                            |   |                  |      |
| 13                         | Bezel                                                                                                              | 13.1 No rust, distortion on the Bezel.<br>13.2 No visible fingerprints, stains or other contamination.                                                                                                                                                                                                                                                                                                                                                      |          |          |                     |        |                            |   |                            |   |                  |      |
| 14                         | Touch Panel                                                                                                        | D: Diameter W: width L: length<br>14.1 Spot: $D < 0.25$ is acceptable<br>$0.25 \leq D \leq 0.4$<br>2dots are acceptable and the distance between defects should more than 10 mm.<br>$D > 0.4$ is unacceptable<br>14.2 Dent: $D > 0.40$ is unacceptable<br>14.3 Scratch: $W \leq 0.03$ , $L \leq 10$ is acceptable,<br>$0.03 < W \leq 0.10$ , $L \leq 10$ is acceptable<br>Distance between 2 defects should more than 10 mm.<br>$W > 0.10$ is unacceptable. |          |          |                     |        |                            |   |                            |   |                  |      |
| 15                         | PCB                                                                                                                | 15.1 No distortion or contamination on PCB terminals.<br>15.2 All components on PCB must same as documented on the BOM/component layout.<br>15.3 Follow IPC-A-600F.                                                                                                                                                                                                                                                                                         |          |          |                     |        |                            |   |                            |   |                  |      |

|    |                                     |                                                                                                                                                                                                                                                                                                                                                         |
|----|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 16 | Soldering                           | Follow IPC-A-610C standard                                                                                                                                                                                                                                                                                                                              |
| 17 | Electrical Defect<br>(Major defect) | <p>The below defects must be rejected.</p> <p>17.1 Missing vertical / horizontal segment,</p> <p>17.2 Abnormal Display.</p> <p>17.3 No function or no display.</p> <p>17.4 Current exceeds product specifications.</p> <p>17.5 LCD viewing angle defect.</p> <p>17.6 No Backlight.</p> <p>17.7 Dark Backlight.</p> <p>17.8 Touch Panel no function.</p> |

Remark: LCD Panel Broken shall be rejected. Defect out of LCD viewing area is acceptable.

### 10.7.Classification of Defects

10.7.1. Visual defects (Except no / wrong label) are treated as minor defect and electrical defect is major.

10.7.2. Two minor defects are equal to one major in lot sampling inspection.

### 10.8.Identification/markings criteria

Any unit with illegible / wrong /double or no marking/ label shall be rejected.


### 10.9.Packing

10.9.1. There should be no damage of the outside carton box, each packaging box should have one identical label.

10.9.2. Modules inside package box should have compliant mark.

10.9.3. All direct package materials shall offer ESD protection.

**Note1:** Bright dot is defined as the defective area of the dot is larger than 50% of one sub-pixel area.



**Bright dot:** The bright dot size defect at black display pattern. It can be recognized by 2% transparency of filter when the distance between eyes and panel is  $350\text{mm} \pm 50\text{mm}$ .

**Dark dot:** Cyan, Magenta or Yellow dot size defect at white display pattern. It can be recognized by 5% transparency of filter when the distance between eyes and panel is  $350\text{mm} \pm 50\text{mm}$ .

**Note2:** Mura on display which appears darker / brighter against background brightness on parts of display area

## 11. Reliability Specification

| No | Item                        | Condition                                                                                     | Quantity | Criteria         |
|----|-----------------------------|-----------------------------------------------------------------------------------------------|----------|------------------|
| 1  | High Temperature Operating  | <b>70°C, 96Hrs</b>                                                                            | 2        | GB/T2423.2-2008  |
| 2  | Low Temperature Operating   | <b>-20°C, 96Hrs</b>                                                                           | 2        | GB/T2423.1-2008  |
| 3  | High Humidity               | <b>50°C, 90%RH, 96Hrs</b>                                                                     | 2        | GB/T2423.3-2006  |
| 4  | High Temperature Storage    | <b>80°C, 96Hrs</b>                                                                            | 2        | GB/T2423.2-2008  |
| 5  | Low Temperature Storage     | <b>-30°C, 96Hrs</b>                                                                           | 2        | GB/T2423.1-2008  |
| 6  | Thermal Cycling Test        | <b>-20°C, 60min~70°C, 60min, 20 cycles.</b>                                                   | 2        | GB/T2423.22-2012 |
| 7  | Packing vibration           | Frequency range:10Hz~50Hz<br>Acceleration of gravity:5G<br>X, Y, Z 30 min for each direction. | 2        | GB/T5170.14-2009 |
| 8  | Electrical Static Discharge | Air: $\pm 8KV$ 150pF/330 $\Omega$ 5 times<br>Contact: $\pm 4KV$ 150pF/330 $\Omega$ 5 times    | 2        | GB/T17626.2-2006 |
| 9  | Drop Test (Packaged)        | Height:80 cm,1 corner, 3 edges, 6 surfaces.                                                   | 2        | GB/T2423.8-1995  |

Note1. No defection cosmetic and operational function allowable.

Note2. Total current Consumption should be below double of initial value.



## 12. Precautions and Warranty

### 12.1. Safety

- 12.1.1. The liquid crystal in the LCD is poisonous. Do not put it in your mouth. If the liquid crystal touches your skin or clothes, wash it off immediately using soap and water.
- 12.1.2. Since the liquid crystal cells are made of glass, do not apply strong impact on them. Handle with care.

### 12.2. Handling

- 12.2.1. Reverse and use within ratings in order to keep performance and prevent damage.
- 12.2.2. Do not wipe the polarizer with dry cloth, as it might cause scratch. If the surface of the LCD needs to be cleaned, wipe it swiftly with cotton or other soft cloth soaked with petroleum IPA, do not use other chemicals.

### 12.3. Storage

- 12.3.1. Do not store the LCD module beyond the specified temperature ranges.
- 12.3.2. Strong light exposure causes degradation of polarizer and color filter.

### 12.4. Metal Pin (Apply to Products with Metal Pins)

#### 12.4.1. Pins of LCD and Backlight

- 12.4.1.1. Solder tip can touch and press on the tip of Pin LEAD during the soldering

#### 12.4.1.2. Recommended Soldering Conditions

Solder Type: Sn96.3~94-Ag3.3~4.3-Cu0.4~1.1



Maximum Solder Temperature: 370 °C

Maximum Solder Time: 3s at the maximum temperature

Recommended Soldering Temp: 350±20 °C

Typical Soldering Time: ≤3s

#### 12.4.1.3. Solder Wetting



#### 12.4.2. Pins of EL

- 12.4.2.1. Solder tip can touch and press on the tip of EL leads during soldering.

- 12.4.2.2. No Solder Paste on the soldering pad on the motherboard is recommended.

#### 12.4.2.3. Recommended Soldering Conditions

Solder type: Nippon Alimit Leadfree SR-34, size 0.5mm

Recommended Solder Temperature: 270~290 °C


Typical Soldering Time: ≤2s

Minimum solder distance from EL lamp (body): 2.0mm

- 12.4.2.4. No horizontal press on the EL leads during soldering.

- 12.4.2.5. 180° bend EL leads three times is not allowed.

#### 12.4.2.6. Solder Wetting




Recommended




Not Recommended

#### 12.4.2.7. The type of the solder iron:




Recommended



Not Recommended

#### 12.4.2.8. Solder Pad



### 12.5. Operation

- 12.5.1. Do not drive LCD with DC voltage
- 12.5.2. Response time will increase below lower temperature
- 12.5.3. Display may change color with different temperature
- 12.5.4. Mechanical disturbance during operation, such as pressing on the display area, may cause the segments to appear “fractured”.
- 12.5.5. Do not connect or disconnect the LCM to or from the system when power is on.
- 12.5.6. Never use the LCM under abnormal condition of high temperature and high humidity.
- 12.5.7. Module has high frequency circuits. Sufficient suppression to the electromagnetic interface shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- 12.5.8. Do not display the fixed pattern for long time (we suggest the time not longer than one hour) because it may develop image sticking due to the TFT structure.

### 12.6. Static Electricity

- 12.6.1. CMOS LSIs are equipped in this unit, so care must be taken to avoid the electro-static charge, by ground human body, etc.
- 12.6.2. The normal static prevention measures should be observed for work clothes and benches.
- 12.6.3. The module should be kept into anti-static bags or other containers resistant to static for storage.

### 12.7. Limited Warranty

- 12.7.1. Our warranty liability is limited to repair and/or replacement. We will not be responsible for any consequential loss.
- 12.7.2. If possible, we suggest customer to use up all modules in six months. If the module storage time over twelve months, we suggest that recheck it before the module be used.
- 12.7.3. After the product shipped, any product quality issues must be feedback within three months, otherwise, we will not be responsible for the subsequent or consequential events.

### **13. Packaging**

TBD

14. Outline Drawing

